



# Zaisains Technologies Sdn Bhd (875930 U)

Level 5, Tower 1, Wisma MCIS Zurich, Jalan Barat, Petaling Jaya, Sel.  
 TEL : 603-79583006 FAX : 603-79583007 Email: sales@zaisains.com

**IT Evolution - Customer service redefined**

## CCTV Cameras

Product Show	Chief Characteristics	Model No.	Specification
	IR LED: $\varnothing$ 5X24PCS IR range: 20M Board Lens 3.6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 86(W) x60(H) x55(D)mm Weight: 400g	LICE24NSL	Color 1/3" SONY 420TVL, Low Illumination Sony 632/633 + Sony 3142
		LICE24NSN	Color 1/3" SONY 480TVL, Low Illumination Sony 632/633 + Nextchip 2030
		LICE24NSHD	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR Sony 638/639 + Nextchip 2040
		LICE24NSHE	Color 1/3" SONY 700TVL, Low Illumination, ATR, OSD, DNR Sony 672/673 + Sony Effio-e
	IR LED: $\varnothing$ 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens (2M Pixels) Water resistance: IP66 3-Axis cable built-in bracket OSD Menu controlled by RS485 (optional) Size: 228(W)x97(H)x82(D)mm Weight: 1.4Kg	LIKT40SL	Color 1/3" SONY 420TVL, Low Illumination Sony 632/633 + Sony 3142
		LIKT40SN	Color 1/3" SONY 480TVL, Low Illumination Sony 632/633 + Nextchip 2030
		LIKT40SHD	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR Sony 638/639 + Nextchip 2040
		LIKT40SHE	Color 1/3" SONY 700TVL, Low Illumination, ATR, OSD, DNR Sony 672/673 + Sony Effio-e
	IR LED: $\varnothing$ 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens (2M Pixels) Water resistance: IP66 OSD Menu controlled by RS485 (optional) DC12V/AC24V double voltage add USD4 Size: 200(W)x171(H)x83(D)mm Weight: 1.4Kg	LIA40ESL	Color 1/3" SONY 420TVL, Low Illumination Sony 632/633 + Sony 3142
		LIA40ESN	Color 1/3" SONY 480TVL, Low Illumination Sony 632/633 + Nextchip 2030
		LIA40ESHD	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR Sony 638/639 + Nextchip 2040
		LIA40ESHE	Color 1/3" SONY 700TVL, Low Illumination, ATR, OSD, DNR Sony 672/673 + Sony Effio-e
	Vandalproof IR Dome Camera IR LED: $\varnothing$ 5X24PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: $\varnothing$ 94 x 69(H) mm Weight: 400g	LIRDBSL	Color 1/3" SONY 420TVL, Low Illumination Sony 632/633 + Sony 3142
		LIRDBSN	Color 1/3" SONY 480TVL, Low Illumination Sony 632/633 + Nextchip 2030
		LIRDBSHD	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR Sony 638/639 + Nextchip 2040
		LIRDBSHE	Color 1/3" SONY 700TVL, Low Illumination, ATR, OSD, DNR Sony 672/673 + Sony Effio-e
	Vandalproof IR Dome Camera IR LED: $\varnothing$ 5X24PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: $\varnothing$ 94 x 80(H) mm Weight: 450g	LIRDNSL	Color 1/3" SONY 420TVL, Low Illumination Sony 632/633 + Sony 3142
		LIRDNSN	Color 1/3" SONY 480TVL, Low Illumination Sony 632/633 + Nextchip 2030
		LIRDNSHD	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR Sony 638/639 + Nextchip 2040
		LIRDNSHE	Color 1/3" SONY 700TVL, Low Illumination, ATR, OSD, DNR Sony 672/673 + Sony Effio-e
	3.7mm Taper Pinhole Lens Size: $\varnothing$ 20 x 62(H) mm Weight: 200g	LBPBSN	Color 1/3" SONY 480TVL, Low Illumination, DWDR, OSD, DNR Sony 632/633 + Nextchip 2030
		LBPBSHD	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR Sony 638/639 + Nextchip 2040